



# PRODUCT DATA SHEET



## PRODUCT NAME/VISCOSITIES: Classic Pistoneeze 10w30

Product No	8145
Issue No.	1
Issue Date	14/08/2019

### DESCRIPTION:

This product is a moderate detergent premium SAE 10w30 multigrade semi synthetic engine oil. High quality solvent refined base oils with latest technology performance additives and shear stable viscosity index improver. It is specifically engineered for classic cars incorporating modern filtration systems, and is formulated with ZDDP (zinc/phosphorus).

### APPLICATION:

Use as received for engine lubrication for classic vehicles, both petrol and diesel, where a multigrade 10w30 is required.

### USER BENEFITS:

- Incorporates modern additive technology with period viscometrics to provide the optimum lubrication characteristics.
- Suitable for higher mileage applications where oil consumption is a problem as high viscosity helps to reduce oil loss and leakage.
- The modern technology ensures an oil which will meet up to date specifications along with meeting the 'period' performance requirements.

### PERFORMANCE PROFILE:

API SL/CF  
ACEA A3/B4  
MB 229.1

### TYPICAL CHARACTERISTICS:

SAE viscosity grade	10w30
Specific gravity at 15°C	0.871
Kinematic viscosity at 100°C	10.2 cSt
Kinematic viscosity at 40°C	61.2 cSt
Viscosity index	154
Pour point °C	<-42
Flashpoint °C	>206
Cold crank viscosity	4000 cP

### HEALTH AND SAFETY:

Health and Safety Data Sheet 8145 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils technical department.

For Technical assistance call +44 (0) 1484 475060 or email [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)